



PENPOWER™ 226H

Page: 1 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

SECTION 1: IDENTIFICATION

Product name: PENPOWER 226H

Recommended use: Cleaner, degreaser

Physical Description: Tan granular powder, virtually odorless

Generic Ingredients: Inorganic builders and surfactants

Manufacturer:

Penetone Corporation
125 Kingsland Ave.
Clifton, NJ 07014
800-631-1652 or 201-567-3000

Business Contact:

Customer Service
800-631-1652 x2602 or 2272
Product Safety
800-631-1652 x2211 or 2257

Emergency Phone Numbers: PENETONE 201-567-3000 CHEMTREC 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

<p>Health: Skin corrosion: 1C Eye damage: 1 Reproductive toxicity: 2</p>	<p>Specific target organ effect - single exposure: 3</p> <p>Physical: not classified</p>
---	---

DANGER!

Causes Severe Skin Burns and Eye Damage.
May Cause Respiratory Irritation.
Suspected of Damaging Fertility.



Precautionary Statements:	
<p><u>Prevention:</u> Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dusts. Use only outdoors or in a well ventilated area. Wear protective gloves, clothing, eye protection, and face protection. Wash hands and exposed skin thoroughly after handling.</p> <p><u>Response:</u> <i>If swallowed:</i> Rinse mouth. Do NOT induce vomiting. <i>If on skin or hair:</i> Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. <i>If in eyes:</i> Rinse cautiously with water for several</p>	<p>minutes. Remove contact lenses, if present and easy to do. Continue rinsing. <i>If inhaled:</i> Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center, doctor, emergency room, or 911. Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical advice/attention.</p> <p><u>Storage:</u> Store locked up.</p> <p><u>Disposal:</u> Dispose of contents/container in accordance with local, regional, and national regulations (see Sections 13 and 15 of SDS for disposal and reporting requirements).</p>

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Concentration Wt% (1)
Sodium carbonate	497-19-8	30-50
Sodium tetraborate pentahydrate	11130-12-4	20-40
Sodium metasilicate	6834-92-0	10-25
Sodium dodecylbenzene sulfonate	25155-30-0	<10



PENPOWER™ 226H

Page: 2 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

Sodium lignosulfonate	8061-51-6	<10
Ethoxylated nonylphenol	127087-87-0	<10

(1) Exact percentages being withheld under trade secret provision of OSHA HCS 1910.1200(I)

SECTION 4: FIRST-AID MEASURES

General Description of Symptoms & First-Aid Measures

Most likely work-place exposure routes will be *skin contact* or *inhalation*.

For *skin contact*, typically no immediate effects will be observed. A tingling or burning sensation might be felt some time after exposure. Slight reddening or minor irritation could also develop if product is not quickly washed off.

Inhalation exposure may produce varied effects, particularly if exposure occurs above the recommended workplace exposure limits (see SECTION 8). Typical symptoms could include coughing, sneezing, and a tingling or burning sensation in the nose, throat, and lungs.

Eyes

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center, doctor, physician or other competent medical authority for medical advice. Penetone recommends that after any eye exposure a physician be seen immediately.

Ingestion

If swallowed: Rinse mouth. **DO NOT INDUCE VOMITING.** Immediately call a poison center, doctor, physician or other competent medical authority for medical advice.

Inhalation

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a local Poison Control Center, physician, or other competent medical authority for medical advice.

Skin

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. A mild soap may be used to wash skin. Wash contaminated clothing before reuse. Immediately call a local Poison Control Center, doctor, physician or other competent medical authority for medical advice.

Special Treatment / Other

None

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification: Non-flammable

Flash Point: None-to-boil

Autoignition Temperature: Not applicable

Lower Flammable Limit: Not applicable **Upper Flammable Limit:** Not applicable

Specific Hazards

Product is a powder and presents no unusual fire hazards.

Extinguishing Media

Use extinguishing agents appropriate for controlling surrounding fire.

Unsuitable: None.

Protection & Precautions for Firefighters

Protective Equipment & Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural



PENPOWER™ 226H

Page: 3 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do it safely. Dike fire control water for later disposal; do not scatter material. Containers can expand and explode under fire conditions due to vapor buildup. Always stay away from containers engulfed in fire.

Hazardous Combustion Products: Smoke, fumes, and oxides of carbon, boron, silicon, and sulfur when burned.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Land Spill

Sweep up material. Put all material into proper waste disposal container with lid tightly covered. Rinse area with plenty of water.

Water Spill

This is a powder will completely mix/dissolve in water making recovery difficult. Undissolved powder should be recovered if possible. This product is alkaline and will raise the pH of surface waters. Localized high concentration of product may cause fish kills, but no persistent or long term effects are anticipated. Check with local environmental regulatory agencies for reporting requirements.

See SECTION 8 for EXPOSURE CONTROLS and PERSONAL PROTECTION.

SECTION 7: HANDLING & STORAGE

Handling

Avoid contact with eyes, skin and clothing. After handling, always wash hands thoroughly with soap and water. Avoid personal contact with any residue. Do not cut, weld, or reuse empty container.

Storage

Store locked up. Keep container tightly closed when not in use. Do not store near strong acids. Do not store in direct sunlight. Avoid storing above 120°F (49°C).

SECTION 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Personal Protection

Inhalation A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. Use of an organic vapor mask or respirator is recommended.

Skin Wear chemical resistant gloves such as: rubber, nitrile, neoprene, or latex when skin contact is possible. Protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn depending on how the product is used. PPE should be cleaned thoroughly after each use.

Eyes Penetone recommends always wearing safety glasses as a minimum in any workplace. Conditions may warrant the use of chemical goggles and possibly a face shield. Consult your standard operating procedure or safety professional for advice. Use protective eye and face devices that comply with ANSI Z87.1-1987.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance



PENPOWER™ 226H

Page: 4 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Occupational Exposure Limits

Component Name	Source	Value	Type	Notation
Sodium metasilicate (1)	ACGIH	2 mg/m ³	Ceiling	
	NIOSH	2 mg/m ³	Ceiling	
	OSHA	2 mg/m ³	TWA	
Borate compounds, inorganic	ACGIH	2 mg/m ³ (1)	TWA	A4
		6 mg/m ³ (1)	STEL	
	NIOSH	1 mg/m ³	TWA	

(1) No OEL has been established for sodium silicate. Because of product pH, value given is for sodium hydroxide.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

- Appearance:** tan granular powder
- Odor:** bland
- Odor Threshold:** not determined
- pH:** not applicable
- Melting Point / Freezing:** not applicable
- Boiling Point / Boiling Point Range:** not applicable
- Flash Point:** not applicable
- Evaporation Rate:** not applicable
- Flammability:** not applicable
- Lower Flammable Limit:** not applicable
- Upper Flammable Limit:** not applicable
- Explosive Properties:** not applicable
- Vapor Pressure:** not applicable
- Relative Vapor Density:** equal to water
- Relative Density:** not applicable
- Solubility (Water):** soluble in water
- Partition Coefficient (K_{ow}):** not determined
- Auto-ignition temperature:** not applicable
- Decomposition temperature:** not applicable
- Viscosity:** not applicable

SECTION 10: STABILITY & REACTIVITY

Reactivity

Product will react with acids. Addition of acid or water to this product may generate large amounts of heat and may cause splattering.

Chemical Stability

Stable.

Hazardous Reactions

Mixing with acids will give off heat and may cause splattering.

[

Conditions to Avoid

Do not store near strong acids.



PENPOWER™ 226H

Page: 5 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

Incompatible Materials

Strong acids.

Hazardous Decomposition Products

Smoke, fumes, and oxides of carbon, boron, silicon, and sulfur when burned.

SECTION 11: TOXICOLOGICAL INFORMATION

Product Summary

This product is an alkaline powder and contains sodium metasilicate. The product should be considered corrosive to all tissues. Contact with skin and/or eyes, ingestion, or inhalation of dust may be corrosive. Possible effects include severe irritation, burns, and permanent damage to exposed tissues if immediate action is not taken.

Acute Toxicity:

Dermal: LD50 > 2,000 mg/kg rabbit (estimated using additivity formula)

Inhalation: No data available

Oral: LD50 > 2,000 mg/kg rat (estimated using additivity formula)

Skin Corrosion/Irritation

Corrosive. Causes skin burns. Prolonged or repeated skin exposures can result in dermatitis.

Serious Eye Damage/Irritation

Corrosive. Causes serious eye damage which can result in severe irritation, pain and burns, and permanent damage including blindness.

Sensitization - Respiratory or Skin

No data for the product. Based upon components, product is not expected to be a respiratory or skin sensitizer.

Germ Cell Mutagenicity

No data for the product. Based upon components, product is not expected to result in germ cell mutagenicity.

Carcinogenicity

Borates are listed by ACGIH as Group 4: Not classifiable as a human carcinogen.

Reproductive / Developmental Toxicity

No data for the product. Insufficient data for the components to evaluate. Based upon partial component data, product is not expected to be a reproductive or developmental toxicant.

The nonionic surfactant used in this product has produced effects in the fetus only at levels that were toxic to the parent animals.

Fetal weight loss and minor skeletal variations have been seen in animal feeding studies. Prenatal development toxicology study of rats an NOEL of 55 mg boric acid/ kg bw was observed. Based on this, classified as a reproductive/developmental toxicant Category 2. No adverse fertility effects were seen in sperm of highly exposed borate workers when a subset of these workers were exposed to 125 mg boron /day. Epidemiological studies of exposed borate workers and populations living in areas with high boron levels were also negative.

Specific Target Organ Effects - Single Exposure

No data for the product.

Specific Target Organ Effects - Repeated or Prolonged Exposure

No data for the product.

Frequent ingestion over extended periods of time of gram quantities of sodium silicate are associated with kidney stone formation and other siliceous urinary calculi in humans.

Chronic study, rat, oral, NOAEL 17.5 mg boron/kg bw/day in chronic feeding study (2 years in rats based on testes



PENPOWER™ 226H

Page: 6 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

effects.) Other effects (kidney, haemopoietic system) seen only at higher dose levels. Classification criteria not met.

Aspiration Hazard

Product form makes it not likely to be an aspiration hazard.

SECTION 12: ECOLOGICAL INFORMATION

Product Summary

This material is alkaline and will raise the pH of surface waters. Product should be considered harmful to aquatic organisms. (Acute aquatic toxicity Category 3 by European Union classification).

Ecotoxicity

LC50/EC50 10-100 mg/l (estimated using additivity formula)

Persistence and Degradability

Inorganic components will dissociate into their ionic form in the aquatic environment. Natural carbon dioxide will slowly neutralize them. The surfactants are biodegradable.

Bioaccumulative Potential

Bioaccumulation potential of the materials used in this product are low.

Other Adverse Effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

The product as received is a nonhazardous waste. Wet powder or solutions may be a D002 Corrosive Hazardous Waste if they have a pH equal to or greater than 12.5. Dispose of contents/container in accordance with all applicable federal, state, and local regulations.

Note: Contaminated product, soil, water, container residues and spill cleanup materials may be hazardous wastes. Appropriate hazardous waste designation is the responsibility of the user.

SECTION 14: TRANSPORT INFORMATION

ID No.: UN3262
Proper Shipping Name: CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (contains sodium metasilicate)
Hazard Class: 8
Packing Group: III
Label: CORROSIVE
Marine Pollutant: No
RQ: 20,000 lbs of product for sodium dodecylbenzene sulfonate
Special Precautions: none

SECTION 15: REGULATORY INFORMATION

TSCA

The ingredients in this product are listed on the TSCA inventory.

RCRA HAZARD CLASS

Nonhazardous waste - see comments in Section 13.



PENPOWER™ 226H

Page: 7 of 7
Date Prepared: September 23, 2019
SDS No.: 1500

SARA 311/312 REPORTABLE HAZARD CATEGORIES: Immediate (Acute) Health

REPORTING REQUIREMENTS (all quantities in pounds)

Component	CAS / 313 Code	Section 302 (EHS) TPQ	Section 304 EHS RQ	CERCLA RQ	Section 313	CAA 112(r) TQ	CWA / OPA
Sodium dodecylbenzene sulfonate	25155-30-0			1,000			
Product RQ for component				20,000			
(1) Releases exceeding the RQ just be reported to the National Response Center, 800-424-8802 and may be subject to state and local reporting.							

NEW JERSEY RIGHT-TO-KNOW INFORMATION

This product contains sodium carbonate (CAS# 497-19-8), sodium tetraborate (CAS# 1303-96-4), sodium metasilicate (CAS# 6834-92-0), sodium dodecylbenzene sulfonate (CAS# 25155-30-0), sodium lignosulfonate (CAS# 8061-51-6), and ethoxylated nonylphenol (CAS# 127087-87-0).

CALIFORNIA PROPOSITION 65 INFORMATION

This product does not contain any chemicals recognized by the state of California to cause cancer and/or birth defects or reproductive harm.

SCAQMD INFORMATION

Is there a photochemically reactive material present? No
What is the % by volume of photochemically reactive material? 0
What is the VOC content? 0
What is the vapor pressure of VOC's? 0

SECTION 16: OTHER INFORMATION

REVISION SUMMARY

Change in Section 1

SUPERSEDES ISSUE DATE

April 1, 2015

HAZARD RATING SYSTEMS:

	<u>HMIS</u>	<u>NFPA</u>
HEALTH	2	2
FLAMMABILITY	0	0
REACTIVITY	0	0
	B	

KEY
4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

FOR ADDITIONAL PRODUCT INFORMATION, CONTACT YOUR SALES ENGINEER
FOR ADDITIONAL HEALTH/SAFETY INFORMATION, CALL 201-567-3000

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND ACCURATE TO THE BEST OF PENETONE'S KNOWLEDGE. THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE.